

PMi 6500



Pramac PMi series inverter: optimal solution to combine silent operation with less fuel consumption and tension stability; the inverters Pramac stabilize the output tension and supply power for all kinds of equipment. They guarantee maximum efficiency: adjusting the speed according to the required load, our inverters reduce the average fuel consumption.

FEATURES

- Inverter technology: stable power for safe operation of sensitive electronics.
- OHV engine provides consistent power for multiple applications.
- Low-oil level shutdown automatically safeguards engine from damage.
- Economy mode automatically adjusts the engine speed to the optimum level to provide excellent fuel economy and noise reduction.
- ATS connector
- Remote control
- 2 wire start
- Lightweight and compact.
- Wheel kit integrated for easy transportation
- Fuel gauge allows user to track gasoline levels



PERFORMANCE

Frequency	Hz	50
Voltage	V	230
Phase		1
Max Power	watt	6500
Rated Power	watt	6000



Engine

Brand	Pramac	
Type	OHV	
Exhaust emission level	Stage V	
Operating Speed Nominal	rpm	Variable
Fuel	Petrol	
Starting Systems	Electric (+Recoil)	
Oil capacity	l	0.85
Low Oil Shutdown	√	



Alternator

Voltage regulation system	Inverter
---------------------------	----------

Dimensional data

Length	(L) mm	625
Width	(W) mm	448
Height	(H) mm	560
Dry weight	kg	50.5
Carton box dimension LxWxH	mm	680x500x610



Autonomy

Fuel tank capacity	14
Fuel consumption 50%	l/h
Running time 50% (Eco Mode)	h



Noise level

Guaranteed noise level (LWA)	dB(A)	96
Noise pressure level @ 7 m	dB(A)	68

GENSET CONTROL

COMMANDS:

- Electric start button
- Smart throttle: Economy mode automatically adjusts the engine speed to the optimum level to provide excellent fuel economy and noise reduction
- ATS connector / 2 wire start / Remote control

INSTRUMENTATION:

- Voltage (V), Frequency (Hz) , Running time (h)
- Oil alarming / output power / Fuel level indicator on the tank
- 12V battery maintainer holder

PROTECTIONS

- Overcurrent / Overspeed / High temperature / AC thermal circuit breaker / DC circuit breaker

OUTPUT:

- DC12V 6A

SOCKET TYPE

SCHUKO 230V 16A IP44	1
2P+T CEE 230V 32A IP44	1



The information is aligned with the Data file at the time of download.
Printed on 09/02/2026 (ID 197302)

©2024 | PR Industrial S.r.l unipersonale – Loc. Il Piano – 53031 Casole d'Elsa (SI) – ITALY. Company subject to the management and coordination of Generac Power Systems Inc. All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice

